

Audible Alarm Beacon



Product Overview

Here is a highly effective way to provide a visual and/or audible indication of an alarm. The combination of alarm and super bright flashing LEDs offer excellent protection for an array of circumstances as they draw attention in a hurry. The sirens and strobes will work in conjunction with our Merlin control panels. For other applications contact Canadian Gas Safety for additional technical information.

Key Features

- Alarm/siren offers 32 selectable sounds and volume control.
- Include high intensity LEDs.
- 8 flash patterns.
- Typical working properties of polycarbonate are -40° to 250F (-40C to 121C).
- Three year guarantee against breakage of polycarbonate in normal use (one year on electro mechanical and electronic components).
- Designed to meet the requirements of IP54.

Construction

- Durable, polycarbonate construction.

Installation

- Operating environment temperatures for CGSAAB models -4F to 140F (-20C to 40C).

Electronics

- 12-24VDC power supply.

Options

- Available with amber, green, blue, red, white, lens.



Audible Alarm Beacon

Function	CGSAAB
Operating Voltage	12VDC-24VDC
Operating Current	0.42A@12VDC, 0.22A@24VDC
Operating Temperature	-4F to 140F (-20C to 60C)
Volume @1 foot (29.4cm)	High 105dB, Low 85dB
8 Flash Patterns	Yes
Strobe Speed Control	No
32 Sounds	Yes
Strobe Only Control	Yes
Sound Only Control	Yes
Alarm Trigger	Trigger on power
9 Volt Battery	No
Low Battery Alert	No
Lens Tamper	N.C. 12VDC, 50mA Dry Contact
Project IP Rating	IP54

Approvals & Warranty

Three year guarantee against breakage of polycarbonate in normal use (one year on electro mechanical and electronic components).

CGSAAB is designed to meet the requirements of IP54.



info@canadiangassafety.com



www.canadiangassafety.com



647-577-1500